

...delivers power and safety to your home and backs up your business!



Features and advantages

- Maximum safety performance with LFP technologies
- Build-in aluminum heat sink, optional heating solutions
- Compact design with flexible size options
- IP 65 protection for indoor and outdoor use
- Compatible with leading inverter brands
- Black start function available, quick installation



Model	Tower T7	Tower T10	Tower T14	Tower T17
Usable Energy	7,1 kWh	10.65 kWh	14.2 kWh	17.76 kWh
Nominal Capacity	37 Ah	37 Ah	37 Ah	37 Ah
Nominal Voltage	288V	384V	480V	576V
Max. Continuous charge Power	7 kW	10 kW	14 kW	17 kW
Max. Continuous discharge Power	7 kW	10 kW	14 kW	17 kW
Net weight	106 kg	149 kg	192 kg	235 kg
Dimension [WxDxH]	612x510x510 mm	800x510x510 mm	988x510x510 mm	1175x510x510 mm
Protection Level	IP 65	IP 65	IP 65	IP 65
Calendar Life [1]	6000 Cycles	6000 Cycles	6000 Cycles	6000 Cycles
Charging Temperature Range	0~45°C	0~45°C	0~45°C	0~45°C
Discharging Temperature Range	-10~45°C	-10~45°C	-10~45°C	-10~45°C
Internal Battery Module	T9637	T9637	T9637	T9637
Module Connection	Series	Series	Series	Series
Module Number	2	3	4	5
Communication	CAN	CAN	CAN	CAN
Warranty	10 years	10 years	10 years	10 years

^[1]Test conditions: 0.2C charge/discharge @+25°C, 80% DOD

